Celox spol. s r.o. Družstevná 1, 900 23 Viničné, Phone: +421 33 647 6573

www.celox.sk, celox@celox.sk

# DECLARATION OF PERFORMANCE no.80

Type of product Balcony profile FLEXI

(1) Product identification code: Product group 39

(2) Serial number: 3959xx

**(3) Intended use:** Al profile is used for edge finishing of balconies and terraces with a completed screed fall.

(4) Manufacturer: Celox spol. s r. o., Záhradná 583/52, 900 23 Viničné

#### **Declaration:**

We hereby declare that for this product group there is no harmonized standard and therefore it is not subject to the CE standard.

#### (9) Declared parameters:

The parameters of the product are specified in technical sheet, which is an integral part of this declaration.

This declaration is issued at sole responsibility of the manufacturer specified in paragraph (4).

Ivan Fischer managing director

Viničné, 1. 7. 2013

**Celox spol. s r.o.**Družstevná 33/a, 900 23 Viničné,
Phone: +421 33 647 6573

www.celox.sk, celox@celox.sk

## PRODUCT TECHNICAL SHEET

## **Balcony profile FLEXI**

## **Short specification**

Balkónový profil z Al

### **Technical parameters**

Length: 2.5 m Colour: natural

Material: Al, 1.3 mm thick

Overhang: 45 mm

Package: box 40 pcs., roll 5 pcs.

The recommended processing temperature is between + 5 °C to 35 °C. Store in dry environment and in horizontal position - to prevent bending.

#### **Material**


#### **ALUMINIUM (AL) natural**


Al material: EN A W 6063 T66, Processing standard: ISO 2768-mk, Tolerance: EN 755-9

The oxidation layer or the darkening of the material results from the effects of air, moisture and alkaline substances. This may be removed with commercially available polishing preparations for this material. After cleaning, these effects may reappear on the surface.

## **Application**

Balcony profile Flexi - is a unique profile on the market with balcony profiles for edge finishing of balconies and terraces with curved shape with placement on completed screed fall. The finishing edge height is 9 mm. It is suitable for construction compositions with one or two component elastic hydro insulation or with separation foil CS. Profile can be bent to a required radius with special bending tool. With the use of sealed edges we get clean and perfect finishing of tiling with curved shape. Profile may be combined with Balcony profile STRAIGHT (PRIAMY).





**Note:** Technical sheet and information specified therein result from our verified tests, long-term experience, knowledge and field use. Celox spol. s r.o. is not responsible for damages caused by incorrect use of the product. Subject to changes.